

Socus

**A SAFER POINT
OF VIEW!**



PRODUCT CATALOGUE

AHD Camera, IP Camera, AHD DVR, NVR, CCTV Power Supply, CCTV Wire



www.socus.co.in

IP CAMERA

ONVIF



3/5MP DOME CAMERA

1/3" HD-CMOS
3.6mm MP HD Lens
IR Distance up to 20-30Mtr.
6-IR Array LED / up to 20-30Mtr...
PoE Optional
H.265 / H.264 Supported
Frame Rate: 3mp@25Fps / 5mp@19fps
Resolution: 3mp@2048P / 5mp@2560P



3/5MP BULLET CAMERA

1/3" HD-CMOS
3.6mm MP HD Lens
IR Distance up to 20-30Mtr.
6-IR Array LED / up to 20-30Mtr...
PoE Optional
H.265 / H.264 Supported
Frame Rate: 3mp@25Fps / 5mp@19fps
Resolution: 3mp@2048P / 5mp@2560P


NVR NETWORK VIDEO RECORDER



H.264 / H.265 NVR

Support 1080 Recording 4/8/16/32 CH
USB2.0 interface
Upto 6TB SATA Interface HDD*1/2/4
Backup, mobile monitoring
PTZ control.
Support, Android, iPhone, Mac.
H.264 / H.265 Supported
HDMI : 1080P (4K)
Support ONVIF protocol

POE SWITCH POWER OVER ETHERNET



4/8/16 PORT POE SWITCH

PoE Ports 1-4/8/16 support
Mode Store-And-Forward
Support Extend 250meters
PoE Standard IEEE 802.3af
Internal power adapter supply
Bandwidth 1.2/2/7.6Gbps (non-blocking)
Two year product warranty

PTZ SPEED DOME CAMERA



2MP AHD/IP PTZ CAMERA

(1/3") / (1/2.9") HD CMOS
2.0 MP HD CMOS
Horizontal Resolution (1920x1080)
6+1 Array IR (Distance up to 150mtr.)
36X Optical Zoom
IP 66 Weather Proof
360 Unlimited Rotation
Stream: Optical, <5Mbps(1080P)
• ONVIF: Supported
Network Interface / Frame rate: 25fps

WIFI CAM SMART WIFI CAMERA



PAN/TILT 360 CAM

Motion Tracker
H.265 Compression
ECO Show
SD Card (64)GB
Crystal Clear Sound
Easy to Connect

AHD CAMERA



2.4/5MP DOME CAMERA

1/3" HD-CMOS
IR Dome Camera
6-Array IR LED
OSD Function Optional
Distance: up to 20-30Mtr.
3.6mm HD Lens (6mm,8mm Optional)
Resolution: 2.4mp@1080P / 5mp@2560P
Frame rate: 2.4mp@25fps / 5mp@19fps
Operating Temperature: -10°C to +55°C

OSD

2.4/5MP BULLET CAMERA

1/3" HD-CMOS
IR Bullet Camera
6-Array IR LED
OSD Function Optional
Distance: up to 20-30Mtr.
3.6mm HD Lens (6mm,8mm Optional)
Resolution: 2.4mp@1080P / 5mp@2560P
Frame rate: 2.4mp@25fps / 5mp@19fps
Operating Temperature: -10°C to +55°C



DVR DIGITAL VIDEO RECORDER



H.265+/H.265 DVR

4/8/16/32CH DVR
Support up to 5MP recording
USB2.0 interfaces / HDD*1/2/4
Backup, mobile monitoring
PTZ control.
Support, Android, iPhone, Mac.
Support LINUX Operating System
IVA Video Analytics
Line Crossing, Object Detection
Dropbox Supported

POWER SUPPLY CCTV POWER SUPPLY



4/8/16CH POWER SUPPLY

4/8/16 Channel
Input Voltage: AC 110-285V
Output Voltage: DC 12V- DC 15V
Efficiency @230V AC: >85%
Input Cord: 2 Pin
Weight: 220/450 Gms.
Input Frequency: 50Hz

GPS DEVICE TRACKING DEVICE



DOWNLOAD
100% FREE APP




SOCUS 140 GPD TRACKER

GPS+IRNSS+LBS+AGPS
Real time tracking
AIS 140 Compliant
Embedded Sim
SOS emergency Call
ACC detection
Remote power control
Remote listen in
• RS232 RS485
Supports 3 IPs

VEHICLE CAM TRANSPORT SECURITY



MOBILE VEHICLE SURVEILLANCE SOLUTIONS





SUPPLEMENTAL LIGHT

LARGE APERTURE

ADVANCED SENSOR